

TITAN T-10 Pressure / Torque Conversion Chart
1-1/2" Square Drive Hydraulic Torque Wrench

| PSI | FT. / LBS. | BAR | KGM | NM |
|------------|-------------------|------------|------------|-----------|
| 1500 | 1662 | 104 | 229 | 2254 |
| 1600 | 1773 | 110 | 245 | 2404 |
| 1800 | 1995 | 124 | 275 | 2705 |
| 2000 | 2236 | 138 | 309 | 3032 |
| 2200 | 2460 | 152 | 339 | 3336 |
| 2400 | 2683 | 166 | 370 | 3638 |
| 2600 | 2907 | 179 | 401 | 3942 |
| 2800 | 3131 | 193 | 432 | 4246 |
| 3000 | 3365 | 207 | 464 | 4563 |
| 3200 | 3589 | 221 | 495 | 4867 |
| 3400 | 3814 | 235 | 526 | 5172 |
| 3600 | 4038 | 248 | 557 | 5476 |
| 3800 | 4263 | 262 | 588 | 5781 |
| 4000 | 4456 | 276 | 615 | 6042 |
| 4200 | 4679 | 290 | 646 | 6345 |
| 4400 | 4902 | 304 | 676 | 6647 |
| 4600 | 5125 | 317 | 707 | 6950 |
| 4800 | 5347 | 331 | 738 | 7251 |
| 5000 | 5588 | 345 | 771 | 7577 |
| 5200 | 5812 | 359 | 802 | 7881 |
| 5400 | 6035 | 373 | 833 | 8183 |
| 5600 | 6259 | 386 | 864 | 8487 |
| 5800 | 6482 | 400 | 895 | 8790 |
| 6000 | 6717 | 414 | 927 | 9108 |
| 6200 | 6940 | 428 | 958 | 9411 |
| 6400 | 7164 | 442 | 989 | 9714 |
| 6600 | 7388 | 455 | 1020 | 10018 |
| 6800 | 7611 | 469 | 1050 | 10321 |
| 7000 | 7746 | 483 | 1069 | 10504 |
| 7200 | 7967 | 497 | 1099 | 10803 |
| 7400 | 8189 | 511 | 1130 | 11104 |
| 7600 | 8410 | 524 | 1161 | 11404 |
| 7800 | 8632 | 538 | 1191 | 11705 |
| 8000 | 8867 | 552 | 1224 | 12024 |
| 8200 | 9089 | 566 | 1254 | 12325 |
| 8400 | 9310 | 580 | 1285 | 12624 |
| 8600 | 9532 | 593 | 1315 | 12925 |
| 8800 | 9754 | 607 | 1346 | 13226 |
| 9000 | 10075 | 621 | 1390 | 13662 |
| 9200 | 10299 | 635 | 1421 | 13965 |
| 9400 | 10523 | 649 | 1452 | 14269 |
| 9600 | 10747 | 662 | 1483 | 14573 |
| 9800 | 10971 | 676 | 1514 | 14877 |
| 10000 | 11067 | 690 | 1527 | 15007 |