

TITAN T-5 Pressure / Torque Conversion Chart
1-1/2" Square Drive Hydraulic Torque Wrench

PSI	FT. / LBS.	BAR	KGM	NM
1500	816	104	113	1106
1600	871	110	120	1181
1800	979	124	135	1328
2000	1104	138	152	1497
2200	1215	152	168	1648
2400	1325	166	183	1797
2600	1435	179	198	1946
2800	1546	193	213	2096
3000	1660	207	229	2251
3200	1771	221	244	2401
3400	1881	235	260	2551
3600	1992	248	275	2701
3800	2103	262	290	2852
4000	2236	276	309	3032
4200	2348	290	324	3184
4400	2460	304	339	3336
4600	2572	317	355	3488
4800	2683	331	370	3638
5000	2808	345	388	3808
5200	2920	359	403	3960
5400	3033	373	419	4113
5600	3145	386	434	4265
5800	3257	400	449	4416
6000	3377	414	466	4579
6200	3489	428	481	4731
6400	3602	442	497	4884
6600	3715	455	513	5038
6800	3827	469	528	5189
7000	3912	483	540	5305
7200	4024	497	555	5457
7400	4135	511	571	5607
7600	4247	524	586	5759
7800	4359	538	602	5911
8000	4532	552	625	6145
8200	4645	566	641	6299
8400	4759	580	657	6453
8600	4872	593	672	6606
8800	4985	607	688	6760
9000	5098	621	704	6913
9200	5211	635	719	7066
9400	5324	649	739	7219
9600	5438	662	750	7374
9800	5551	676	766	7527
10000	5647	690	779	7657

Titan Technologies - 130 Fort Path Road (Suite 9) Madison, CT 06443
 Phone: (203)245-8484 Fax: (203)245-8988 Email: sales@titanti.com